US010736542B2

(12) **United States Patent**
Krimmer et al.

(10) **Patent No.: US 10,736,542 B2**
(45) **Date of Patent: Aug. 11, 2020**

(54) **INSOLE OR SHOE SOLE**

(71) Applicant: **stAPPtronics GmH**, Sulz (AT)

(72) Inventors: **Peter Krimmer**, Vienna (AT); **Philip Olbrich**, Vienna (AT); **Thomas Frois**, Sulz (AT)

(73) Assignee: **stAPPtronics GmH**, Sulz (AT)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 304 days.

(21) Appl. No.: **15/716,958**

(22) Filed: **Sep. 27, 2017**

(65) **Prior Publication Data**

US 2018/0085030 A1 Mar. 29, 2018

(30) **Foreign Application Priority Data**

Sep. 27, 2016 (AT) 443/2016

(51) **Int. Cl.**
A61B 5/103 (2006.01)
A43B 13/12 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***A61B 5/1036*** (2013.01); ***A43B 3/0005*** (2013.01); ***A43B 3/0031*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC ... A61B 5/1036; A61B 5/6829; A43B 17/006; A43B 13/12; A43B 3/0031; A43B 13/37; A43B 3/0005; A43B 13/14
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,195,921 B1 3/2001 Truong
2005/0217142 A1 10/2005 Ellis, III
(Continued)

FOREIGN PATENT DOCUMENTS

CN 103169598 6/2013
CN 104172641 12/2014
(Continued)

OTHER PUBLICATIONS

https://www.kickstarter.com/projects/smartmove/smartmove-accuracy-you-can-trust-change-made-easy?ref=nav_search&result=project&term=smartmove, May 23, 2014.
(Continued)

Primary Examiner — Christian Jang
(74) *Attorney, Agent, or Firm* — Volpe and Koenig, P.C.

(57) **ABSTRACT**

Insole or shoe sole, which has a sensor device (**10**) having a plurality of sensor fields (**1-9**) for pressure detection and an electronic unit (**15**) that is electrically connected to the sensor fields (**1-9**) and has electronic components (**17**), wherein the sensor device (**10**) is formed in the manner of a sandwich with a middle layer (**12**) made of a piezoresistive material, a top layer (**13**) arranged above the middle layer (**12**) and a bottom layer (**11**) arranged underneath the middle layer (**12**). The top and bottom layer (**13**, **11**) each include an electrically conductive material (**14**) in the region (**1***a*-**9***a*; **1***b*-**9***b*) of a respective sensor field (**1-9**). The top and bottom layer (**13**, **11**) each have a protruding flexible tab (**23**, **22**) having conductor tracks (**24-26**) for electrically connecting the sensor fields (**1-9**) to the electronic unit (**15**). The electronic unit (**15**) has contact regions (**29**), against which the tabs (**23**, **22**) bear by way of their conductor tracks (**24-26**).

11 Claims, 5 Drawing Sheets